darren@fuelco-sa.com | fuelco-sa.com



## **Kube - LTKU 6,000**



- Comes complete with fluid level dipstick, vent pipe and fittings
- Baffled internally
- Lockable containment area for pump, hose and nozzle storage
- The number of standard feed and return line portsallow for the connection of up to 3 x generators or industrial equipment simultaneously
- Designed to be stacked for storage and transport empty
- Can be lifted via forklift to ensure ease of access and maneuverability; as well as lifting eyes at each corner

## **Specifications**

Description	
Capacity, litres	6,000
Length, mm	3,574
Width, mm	2,274
Height, mm	1,254
Tare Weight, kg	2,050
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	UL142, ULCS601 AS1940, AS1692

Optional dispensing and metering available. Custom Solar option



Disclaimer: Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras

## **GLOBAL CONTACTS**

MIDDLE EAST: +971 50 719 7137 | ASIA: +61 430 531 448 | AUSTRALIA: +61 3 9775 1366

**SOUTH AMERICA:** +56 9 9219 1598 | **CENTRAL AMERICA:** +50 5 2277 3216